



POINT-TO-POINT

Standard Microwave Combiner 6-40 GHz

HIGH-PERFORMANCE POINT-TO-POINT MICROWAVE COMBINERS

Overview

The SMC family of standard microwave combiners are waveguide combiner/couplers that allow sharing a single antenna between two ODUs, with both ODUs using the same polarization. Vertical polarization is standard, but horizontal polarization may be used with the included polarization changer (except 6 GHz).

Both ODUs use direct mount slip fit waveguide connections with standard latches. The antenna connection can be direct mount slip fit (Standard models) or remote mount waveguide flange interface (-R option). The antenna mount versions utilize compression latches and bolts for increased strength, and are compatible with Trango -S2, -R2 and -R3 antenna models.

Highlights

- » V or H combiner for HP ODUs
- » Direct or remote antenna mount
- » Symmetrical and asymmetrical loss versions available
- » Heavy duty construction
- » Antenna latches and bolts for superior strength
- » Available in remote mount (-R) version with standard waveguide flange

Applications

- » Dual polarization 4+0 applications
- » Single polarization 2+0 applications
- » 1+1 hot standby and frequency diversity applications
- » Reuse of existing antennas for higher capacity with standard waveguide antenna port



Specifications

MODEL #	Frequency Range	Insertion Loss (dB max) ODU1	Insertion Loss (dB max) ODU2	- R Option Flange
SMC-06-3-HP	5.9-7.1 GHz	3.3	3.3	CPR137F/UDR70 (WR137)
SMC-78-3-HP	7.1-8.5 GHz	3.3	3.3	CPR112F/UDR84 (WR112)
SMC-11-3-HP	10.7-11.7 GHz	3.3	3.3	CPR90F/UDR100 (WR90)
SMC-13-3-HP	12.7-13.3 GHz	3.3	3.3	UBR120 (WR75)
SMC-15-3-HP	14.4-15.4 GHz	3.3	3.3	UBR140 (WR62)
SMC-18-3-HP	17.7-19.7 GHz	3.3	3.3	UBR220 (WR42)
SMC-23-3-HP	21.2-23.6 GHz	3.3	3.3	UBR220 (WR42)
SMC-26-3-HP	24.2-26.5 GHz	4.1	4.1	UBR220 (WR42)
SMC-28-3-HP	27.5-29.5 GHz	4.1	4.1	UBR320 (WR28)
SMC-32-3-HP	31.8-33.4 GHz	4.1	4.1	UBR320 (WR28)
SMC-38-3-HP	37.0-40.0 GHz	4.1	4.1	UBR320 (WR28)
SMC-06-6-HP	5.9-7.1 GHz	1.9	6.5	CPR137F/UDR70 (WR137)
SMC-78-6-HP	7.1-8.5 GHz	1.9	6.5	CPR112F/UDR84 (WR112)
SMC-11-6-HP	10.7-11.7 GHz	1.9	6.5	CPR90F/UDR100 (WR90)
SMC-13-6-HP	12.7-13.3 GHz	1.9	6.5	UBR120 (WR75)
SMC-15-6-HP	14.4-15.4 GHz	1.9	6.5	UBR140 (WR62)
SMC-18-6-HP	17.7-19.7 GHz	1.9	6.5	UBR220 (WR42)
SMC-23-6-HP	21.2-23.6 GHz	1.9	6.5	UBR220 (WR42)
SMC-26-6-HP	24.2-26.5 GHz	1.9	6.5	UBR220 (WR42)
SMC-28-6-HP	27.5-29.5 GHz	1.9	8.0	UBR320 (WR28)
SMC-32-6-HP	31.8-33.4 GHz	1.9	8.0	UBR320 (WR28)
SMC-38-3-HP	37.0-40.0 GHz	4.1	8.0	UBR320 (WR28)
Return Loss (all models)				> 16 dB
ODU Isolation (all models)				> 20 dB
ENVIRONMENTAL				
Temperature	-40° to +65° C (Operating), -40° to +75° C (Storage)			
Sealing Pressure	5 psi			
RoHS Compliance	Yes			
MECHANICAL				
Size (including radios)	13.58" x 10.43" x 11.42" (34.5 x 26.5 x 29 cm)			
Weight (including radios)	26.55 lbs/12.04 kg			
Antenna Attachment	M8 Stainless Bolts (4) plus 4 Compression Latches			
Material	6061-T6 Aluminum (powder coated)			
Finish	Corrocoat White Powder Coat			



© Trango Systems, Inc. All rights reserved. Trango and TrangoLINK are registered trademarks of Trango Systems, Inc. All other marks are the property of their respective owners. Trango continually improves products as new technologies and components become available. Trango, therefore, reserves the right to change specifications without prior notice. All features, functions and operations described herein may not be marketed in all parts of the world. Consult your Trango representative for further information.

14118 Stowe Dr., Suite B, Poway, CA 92064 | Tel.: +1 (858) 391-0010 | Fax: +1 (858) 391-0020 | Email: sales@trangosys.com

WWW.TRANGOSYS.COM

DS-1020-A